



**EEEEASILY
MORE.**

Excellent. Efficient. Expert.

The value-added modules of the IBC SOLAR Line.

IBC MonoSol 370 CS9-HC, 375 CS9-HC

First-class solar modules made of monocrystalline half-cut-cells



25 year linear power and
15 year product warranty¹



Positive power tolerance (-0/+5)



Increased mechanical stability (5400 Pa)



German warrantor



100% tested quality



Improved shadowing management
thanks to half-cut-technology

IBC SOLAR – your partner for energy solutions

IBC SOLAR AG has had a successful presence in the photovoltaic market for **more than 35 years** and is one of the leading international energy companies providing high-performance system solutions in every size and for every application with intelligent photovoltaic systems. The **economic strength and financial independence** is confirmed by globally recognised rating agencies.

Smart Systems for Solar Power thanks to perfectly matched components. **More than 1,000 highly qualified partners** around the world, as well as **more than 4,200 megawatts of installed power**, which supply **around 2 million people with solar power**, underline the high level of expertise of IBC SOLAR.

IBC SOLAR – leading PV system integrator from Germany since 1982!

TECHNICAL DATA

IBC MonoSol	370 CS9-HC	375 CS9-HC
Article number	2003800028	2003800029

Electrical data (STC):		
STC Power P _{max} (Wp)	370	375
STC Nominal Voltage U _{mp} (V)	34.08	34.26
STC Nominal Current I _{mp} (A)	10.88	10.95
STC Open Circuit Voltage U _{oc} (V)	41.31	41.54
STC Short Circuit Current I _{sc} (A)	11.41	11.5
Module Efficiency (%)	20.3	20.59
Power Tolerance (Wp)	-0/+5	-0/+5

Electrical data (NOCT):		
800 W/m ² NOCT AM 1.5 Power P _{max} (Wp)	275	279
800 W/m ² NOCT AM 1.5 Nominal Voltage U _{mp} (V)	31.8	32.0
800 W/m ² NOCT AM 1.5 Open Circuit Voltage U _{oc} (V)	38.5	38.7
800 W/m ² NOCT AM 1.5 Short Circuit Current I _{sc} (A)	9.68	9.78
Relative Efficiency Reduction at 200 W/m ² (%)	4.19	4.26

Temperature coefficient:		
NOCT (°C)	42	42
Tempcoeff I _{sc} (%/°C)	+0.059	+0.059
Tempcoeff V _{oc} (mV/°C)	-118.97	-119.64
Tempcoeff P _{mp} (%/°C)	-0.381	-0.381


Operating conditions:	
Max. System Voltage (V)	1500
Application Class	A
Reverse Current I _r (A)	25
Current value string fuse (A)	20
Fuse protection from parallel strings	3

Mechanical properties:	
Dimensions (L × W × H in mm)	1755 × 1038 × 40
Weight (kg)	20.0
Max. Test load, Push/Pull (Pa)	5400/2400
Max. Design load ² , Push/Pull (Pa)	3600/1600
Front sheet (mm)	3.2 (low-iron photovoltaic glass and anti-reflective coating)
Frame	anodized aluminium, sturdy hollow-chamber frame
Cells	12 × 10 mono-crystalline silicon cells
Connection type	EV02

Warranties and certification:	
Product warranty	15 years ¹
Power warranty	25 years, linear ¹
Certification	IEC 61215, IEC 61730-1/-2, ISO 9001, ISO 14001, OHSAS 18001


Packaging information:	
Number of modules per pallet	27
Number of pallets per 40' container	26
Dimensions incl. pallet (L × W × H in mm)	1795 × 1145 × 1196
Gross weight incl. double pallet (kg)	595
Stackability per pallet	2-fold

25 year linear power warranty by IBC SOLAR



¹) The linear power and product warranty are only valid for installations within Europe and Japan. The warranty requires installation according to the valid installation instructions. Standard test conditions: 1000 W/m² irradiation with a spectral distribution of AM1.5 and a cell temperature of 25°C. 800 W/m², NOCT. Information according to EN60904-3 (STC). All values according to DIN EN 50380. Errors and changes reserved.
 The precise conditions and content can be taken from the respectively valid version of the product and power warranty, which you can obtain from your IBC Premium Partner.

²) Loads according to IEC 61215-2:2016, max. design load



Presented by: